



SEAGULL® IV X-1, X-2 Designer Series and X-6 Drinking Water Purification Systems

General Ecology presents data from testing specifically selected to demonstrate product effectiveness in removing those contaminants most frequently encountered in water supplies. Please note that all General Ecology, Inc's test results represent performance *using actual contaminants, not substitute surrogates.*

This Performance Data Sheet shows some of the removal capabilities of the SEAGULL® IV products. It is recommended that before purchasing a water treatment unit you have your water supply tested to determine your actual water treatment needs.

Product Brand Names

Seagull IV X-1	Drinking Water Purification System, Configuration B, F, P
Seagull IV X-2	Designer Series Drinking Water Purification System, Configuration B, KB, KF
Seagull IV X-6	Drinking Water Purification System

Manufacturer

All Seagull IV Drinking Water Purification Systems are manufactured in the USA by:
General Ecology, Inc.
151 Sheree Boulevard
Exton, PA 19341-1292

Operating Conditions

	X-1	X-2	X-6
Housing Material	Stainless Steel.....	Stainless Steel.....	Stainless Steel
Cartridge	RS-1SG.....	RS-2SG.....	RS-6SG
Particle Retention	0.4 micron.....	0.4 micron.....	0.4 micron
Pressure (psig) min/max	25/125.....	25/125.....	25/125
Flow Rate (gpm @ 30 psi)	1.....	2.....	6
Average Capacity (gals)	1,000.....	2,000.....	6,000
Temp (F) min/max	33/100.....	33/100.....	33/100
pH min/max	5/9.....	5/9.....	5/9

- No electricity is required.
- Do not freeze unit.
- Flow rate and capacity will depend on operating conditions and source water characteristics.
- The cartridge should be replaced annually, when the flow rate drops to an inconvenient level or if tastes and odors should become evident.

Aesthetic Water Quality Improvement

Seagull IV Drinking Water Purification Systems also remove the following, which some individuals may find offensive in drinking water: • **Chlorine** • **Foul Tastes** • **Color** • **Foul Odors** • **Turbidity**

Test Conditions

All tests were conducted under standard operating conditions as previously stated for the rated capacity of the cartridge.

Performance Notice

These data are based on documented results from specific testing and generally are regarded as indicative of effectiveness to be expected, but are not specific claims of performance. Performance may vary due to water characteristics and system operating conditions.

Test Data

Testing was conducted for the full rated capacity using the actual contaminant listed. No Surrogates were used.

Contaminant Filtered	Influent	Effluent	Detection Level	MCL ⁺
Organic Chemicals				
1,1,2-Trichloroethane	20 ppb	ND	2 ppb	5 ppb*
1,2-Dibromomethane (EDB)	1.9 ppb	ND	2 ppb	5 ppb
1,4-Dichlorobenzene	73 ppb	ND	NSF Standard 53	5 ppb ⁺⁺
2,4,5-TP (Silvex)	30.6 ppb	ND	.05 ppb	10 ppb
2,4-D	338 ppb	ND	1 ppb	70 ppb
Aldicarb (Temik)	228 ppb	ND	1 ppb	7 ppb ⁺⁺
Carbon Tetrachloride	20 ppb	0.6 ppb		5 ppb
Chlordane	50 ppb	ND	1 ppb	20 ppb
Chlorine Residual	500 ppb	ND	50 ppb	2.5 ppm (not an MCL)
Methoxychlor	240 ppb	ND	.05 ppb	40 ppb **
P-chlorobenzene	10 ppb	ND	1 ppb	5 ppb proposed *
PCB	0.05 ppb	ND	01 ppb	--
Tetrachlorethylene (PCE)	73 ppb	ND	NSF Standard 53	5 ppb
Trichloroethylene (TCE)	328 ppb	ND	NSF Standard 53	5 ppb
Trihalomethane Total	92 ppb	ND	1 ppb	100 ppb**
ND - None Detected				

Test Data

Testing was conducted for the actual contaminant listed. No Surrogates were used.

Contaminant Filtered	Influent	Effluent	Detection Level	MCL ⁺
Microbiological				
	(colonies/100 ml)	(colonies/100 ml)	(colonies/100 ml)	(colonies/100 ml)
Campylobacter jejuni	1.6-3.0 x 10 ⁷	ND	10	--
Cryptosporidium	1 ⁻³ x 10 ⁵	ND	1	--
Escherichia coli	10 ⁷	ND	1	0/100 ml
Escherichia coli 0157:H7	10 ⁷	ND	10	0/100 ml
Fecal Coliform	10 ³	ND	1	0/100 ml
Giardia lamblia	1.13 x 10 ⁵⁺⁺⁺	ND	1	--
Listeria monocytogenes	2.2-2.8 x 10 ⁷	ND	10	--
Poliovirus and Rotavirus	6.3 x 10 ⁵ -2.8 x 10 ⁶	ND-320 pfu	11 pfu	--
Pseudomonas aeruginosa [§]	10 ³	ND	1	--
Salmonella typhi [§]	10 ⁵	ND	1	0/100 ml
Yersinia enterocolitica	2.0-2.8 x 10 ⁵	ND	10	--
ND - None Detected				

Test Data

Testing was conducted for the actual contaminant listed. No Surrogates were used.

Contaminant Filtered	Influent	Effluent	Detection Level	MCL ⁺
	<i>Original Well Water</i>	<i>Tested Filtered Water</i>		
Aesthetics				
Color	20	0	--	--
Hardness	72 mg/L	66 mg/l	--	--
Odor	abnormal	normal	--	--
Taste	abnormal	normal	--	--
Turbidity	2	0	--	--
ND - None Detected				

Extraction Data

Leaching tests comply with NSF Standard 53

Contaminant Leached	Testing Protocol	Result	Detection Level
<p>Systems have been evaluated, tested and comply with NSF/ANSI Standard 53-2010 requirements for extraction of volatiles, semi-volatiles and metal.</p>			

- ⁺ Maximum Contaminant Level of Federal Standards shown unless a more rigorous standard is indicated.
- ⁺⁺ New York Maximum Contaminant Level is more rigorous than Federal level.
- ⁺⁺⁺ Total per 500 gallons.
- [§] Sampled at less than rated capacity.
- ^{*} Journal AWWA, February 1992.
- ^{**} Water Technology, August 1991.

Note: Intended not to remove dissolved salts and minerals. Various Federal, State and Local regulations may become known or change and affect distribution and presentation of performance claims. All health claims not in compliance with local or state laws are hereby withdrawn.

Installation Instructions

The SEAGULL® IV Drinking Water Purification System is designed to connect to the cold water supply and also can connect directly to the main faucet or an auxiliary faucet depending upon configuration selection. Please see the Installation And Product Use Instructions for diagrams and detailed step-by-step directions.

Warranty Statement

Every SEAGULL® IV Purification System stainless steel pressure vessel is warranted for ten years, from the date of purchase, to be free from defects in materials and workmanship when installed and operated according to General Ecology Incorporated's detailed instructions. For service under this warranty, please contact your SEAGULL® IV dealer or General Ecology, Inc.

This warranty does not apply to damage to these products resulting from accident, misuse, tampering, corrosion, modification or incorrect installation. Cartridge capacity and performance will vary depending upon water characteristics and for this reason, specifically are not covered by this warranty.

Customer Satisfaction/Money Back Guarantee

We stand behind the quality and effectiveness of our SEAGULL® IV Drinking Water Purification Systems. If you are not fully satisfied with your system, simply return it to the point of purchase within 30 days, undamaged, for a FULL REFUND of purchase price.

Standards Conformance

SEAGULL® IV Purification Systems have been tested and conform to the following industry standards:

- Pressure Vessel Integrity: American Society of Mechanical Engineers, Section 8
- Materials of Construction: American Society of Testing Materials A 167, ASTM B16, ASTM D2000
- Non-leaching Standards: NSF 53
- Materials in Water Contact Applications: USFDA
- State Requirements: - New York Testing Protocol - Wisconsin Plumbing Codes
- Massachusetts Plumbing Codes

- NSF53 - Pertinent Sections

- Overall Product Safety and Effectiveness Verification:

Analytical Consulting Service, Inc. Kensington, MD USA

Betz, Converse, Murdoch, Inc. Plymouth Meeting, PA USA

Colorado State University Fort Collins, CO USA

Field Epidemiology Survey Team Miami, FL USA

Food Quality Lab/Pacific Pure Water, Inc. Honolulu, HI USA

Food Research Institute Madison, WI USA

General Ecology Water Research Lab Exton, PA USA

Marine Testing Institute Mamaroneck, NY USA

Marist College Research Institute Poughkeepsie, NY USA

National Testing Laboratories, Inc. Cleveland, OH USA

Rockaway Township Health Department Rockaway, NJ USA

Roy Weston Laboratories West Chester, PA USA

Spectrum Labs Fort Lauderdale, FL USA

State of Massachusetts Massachusetts USA

State of Wisconsin Madison, WI USA

Suffolk County NY Health Department Hauppauge, NY USA

Tighe & Bond Easthampton, MA USA

United States Army Biomedical R&D Lab Fort Detrick, Frederick, MD USA

United States Testing Company, Inc. Tulsa Division, OK USA

Villanova University Villanova, PA USA

Australian Water Board Sydney, Australia

Department of Public Health London, United Kingdom

Food & Hygiene Association Tokyo, Japan

Hungarian Health Ministry Budapest, Hungary

Institut Pasteur Paris, France

Italian Ministry of Health Rome, Italy

National Defense Headquarters Ottawa, Canada

Tokyo Food Sanitation Association Tokyo, Japan

TÜV German Technical Institute Germany

- **General Ecology, Inc.**

151 Sheree Blvd.

Exton, PA 19341 USA

610-363-7900 phone

610-363-0412 fax

800-441-8166 customer service

www.generalecology.com

Distributed By:

General Ecology, Inc.

the pure science of safe water™



151 Sheree Blvd., Exton, Pennsylvania 19341 USA

(610) 363-7900 fax (610) 363-0412 www.generalecology.com